

Beacons

Flashing LED

Klaxon 45 Series

45 Series Flashing LED beacons are visual indicators suitable for use in indoor and outdoor applications.

All 45 Series beacons are fitted with a diffuser for greater visibility and spread of light.

They include a terminal block and a 27mm deep base mounting with a seal and grommet.

An upgrade kit (with cable connector) is available to upgrade the product from IP65 rating to IP67.

Features and Specifications

- LED light source
- Compact, ultra modern sleek appearance
- IP65 rated; IP67 rated (with upgrade kit)
- White, high quality polycarbonate housing
- Suitable for use in indoor and outdoor applications
- Vandal-resistant safety locking mechanism
- Operating temperature range: -4°F to 158°F (-20°C to +70°C)




3.346"



Ordering Information						
Description	Edwards Cat. No.	Klaxon Cat. No.	Operating Voltage	Current	Lens Colors	Flash Rate
LED Beacon Flashing	45-711811	QBS-0012	110V AC	0.032 A	Red	60 fpm
	45-711821	QBS-0013	110V AC	0.032 A	Amber	60 fpm
	45-711831	QBS-0014	110V AC	0.032 A	Clear	60 fpm
	45-711841	QBS-0015	110V AC	0.032 A	Blue	60 fpm
	45-711851	QBS-0016	110V AC	0.032 A	Green	60 fpm
	45-712811	QBS-0027	230V AC	0.032 A	Red	60 fpm
	45-712821	QBS-0028	230V AC	0.032 A	Amber	60 fpm
	45-712831	QBS-0029	230V AC	0.032 A	Clear	60 fpm
	45-712841	QBS-0030	230V AC	0.032 A	Blue	60 fpm
	45-712851	QBS-0031	230V AC	0.032 A	Green	60 fpm

Accessories		
Description	Edwards Cat. No.	Klaxon Cat. No.
IP67 Upgrade Kit (AC)	45-710001	QBO-0005



VISUAL SIGNALS

Beacons

Flashing LED

Klaxon 45 Series

Weights and Dimensions

Edwards Cat. No.	Klaxon Cat.No.	Approx. Net Weight (lb.)
45-711811	QBS-0012	0.31
45-711821	QBS-0013	0.31
45-711831	QBS-0014	0.31
45-711841	QBS-0015	0.31
45-711851	QBS-0016	0.31
45-712811	QBS-0027	0.31
45-712821	QBS-0028	0.31
45-712831	QBS-0029	0.31
45-712841	QBS-0030	0.31
45-712851	QBS-0031	0.31

