

Outdoor Warning Systems

Control Valves

KB Series



Solenoid and combination solenoid/manual control valves are designed for use with Edwards Airchime air horns.

Features and Specifications

Solenoid Valves

- Local or remote operation
- Class 1, Div. 1, Groups C and D; Class II, Div. 1, Groups E, F and G approvals

Combination Valves

- Manual and solenoid control
- Class 1, Div. 1, Groups C and D; Class II, Div. 1, Groups E, F and G approvals
- Provides for operation in the event of a power failure

| Ordering Information | | | |
|-----------------------|----------|-------------------|-------------------|
| Description | Cat. No. | Operating Voltage | Pipe Thread (in.) |
| Solenoid Valve | 10746-N5 | 120V AC | 3/8 |
| | 10748-N5 | 120V AC | 1/2 |
| | 10750-N5 | 120V AC | 3/4 |
| | 10754-N5 | 120V AC | 1 1/4 |
| | 10746-G1 | 24V DC | 3/8 |
| | 10748-G1 | 24V DC | 1/2 |
| | 10750-G1 | 24V DC | 3/4 |
| | 10754-G1 | 24V DC | 1 1/4 |
| Solenoid/Manual Valve | 10775-N5 | 120V AC | 3/8 |
| | 10776-N5 | 120V AC | 1/2 |
| | 10777-N5 | 120V AC | 3/4 |
| | 10778-N5 | 120V AC | 1 1/4 |
| | 10775-G1 | 24V DC | 3/8 |
| | 10776-G1 | 24V DC | 1/2 |
| | 10777-G1 | 24V DC | 3/4 |
| | 10778-G1 | 24V DC | 1 1/4 |



Outdoor Warning Systems

Control Valves

KB Series

Weights and Dimensions

| Cat. No. | Approx. Shipping Weight (lb.) |
|----------|-------------------------------|
| 10746-N5 | 2.1 |
| 10748-N5 | 2.1 |
| 10750-N5 | 2.1 |
| 10754-N5 | 2.1 |
| 10746-G1 | 2.1 |
| 10748-G1 | 2.1 |
| 10750-G1 | 2.1 |
| 10754-G1 | 2.1 |
| 10775-N5 | 2.1 |
| 10776-N5 | 2.1 |
| 10777-N5 | 2.1 |
| 10778-N5 | 2.1 |
| 10775-G1 | 2.1 |
| 10776-G1 | 2.1 |
| 10777-G1 | 2.1 |
| 10778-G1 | 2.1 |