

Horns Projector B93 Class



The B-KM-8130 Series is a heavy-duty, high decibel, vibrating horn signal designed for use in hazardous locations.

Two mounting lugs are provided on either side of the unit for wall mounting. The housing is tapped on one side for 1/2" (13mm) conduit to allow for field wiring installation.

Features and Specifications

- Intermittent Duty Cycle: 5 minutes on/ 5 minutes off
- Corrosion resistant electrostatic heat flowed epoxy finish
- Cast aluminum housing and ring
- Seamless steel projector
- 5" (127mm) spring steel diaphragm
- 5 1/2" (140mm) projector
- UL listed for Class 1, Div. 1 and 2, Groups C and D; Class II Div. 1 and 2, Groups E, F and G; and Class 1, Groups A and B, Div. 2 locations

Ordering Information

Description	Cat. No.	Operating Voltage ¹	Current	VA	dB at 1m/10ft.	Coil Res (Ohms)
Single Projector	B-KM-8130-G5	24V AC	2 A	48	115/105	1
	B-KM-8130-N5	120V AC	0.45 A	54	115/105	24

¹AC voltage frequency is 60 Hz.

Weights and Dimensions

Cat. No.	Approx. Net Weight (lb.)	Approx. Shipping Weight (lb.)
B-KM-8130-G5	7.00	8.00
B-KM-8130-N5	7.00	8.00

